## Fristam FL3



## Fristam rotary lobe pumps FL3

Superior performance, transfer and CIP in one pump. The FL3's unique three-wing rotor design expands the application range of the FL positive displacement pumps. Its helical rotors virtually eliminate pulsation, ensuring gentle product handling as well as allowing higher transfer capacity and effective CIP.

## SPECIFICATIONS FRISTAM FL3 100L \*

Design	Rotary lobe pump with counter-rotating rotors designed to handle viscous and non-viscous products.	
Construction	Special three-wing design helical rotors allow safe and gentle product handling and virtu- ally eliminate pulsation. Consequently the pump operates at faster speeds and reduced noise.	
Advantages	Smooth operation. Higher flow rates achie- ved with the same pump size. Dual duty, using only one pump for product and CIP operation. Gentle product handling.	
Max. revolution speed (water) Max. revolution speed (product)	~800 to 1000 min <sup>-1</sup> ~700 min <sup>-1</sup>	BENEFITS
Max. discharge flow (water) Max. discharge flow (product)	~50 m³/h ~35 m³/h	<ul><li> Improved performance and reduced associated costs</li><li> Low pulsation</li></ul>
Max. discharge pressure	8 bar	<ul> <li>Product and CIP operation</li> </ul>
Max. system pressure	12 bar	using only one pump
Displacement	1,1 liter/revolution	
Rotating direction	Reversible	
Max. temperature	95° C	
Mounting	Horizontal and vertical	
Connection (nominal diameter)	DN 80	
Connection type	To suit requirements	
Material	Stainless steel 1.4404 (316L), alternative materials possible	
Gasket material	FKM, NBR, EPDM, alternative materials possible	
Mechanical seal	Single / flushed	
Mechanical seal material	Carbon / Stainless Tungsten Carbide / Tungsten Carbide Silicon Carbide / Silicon Carbide	

\*) Please note that technical information provided above is subject to further development of the product range.

Fristam Pumps UK Limited Partnership Unit 11 APEX Business Park Diplocks Way, Hailsham East Sussex BN27 3JU Great Britain Tel +44 (0)1323 849 849 Fax +44 (0)1323 849 438 E-Mail sales@fristam.co.uk For international contact information, please visit www.fristam.de.

